

**????????????? REFCO REF-LOCATOR 4686714 ## ?????????????? ##**



????????????? REFCO REF-LOCATOR 4686714



????????????? REFCO REF-LOCATOR 4686714 Technical Data: Sensitivity: 0.05 oz/yr All HFC, refrigerants and blends including HFC's R410A, R404A, R407C, & R134a 0.025 oz/yr HCFC R22. 0.0125 oz/yr HFO R-1234yf Also indicates HC refrigerants Inspection Light:

?????????????: ??? ?????????????? ??????  
?????

[????????? ??? ?? ???????](#)

????????????? Technical Data:

- Sensitivity: 0.05 oz/yr All HFC, refrigerants and blends including HFC's R410A, R404A, R407C, & R134a  
0.025 oz/yr HCFC R22.  
0.0125 oz/yr HFO R-1234yf  
Also indicates HC refrigerants
- Inspection Light: 6 white LED's.  
Auto shutoff after 5 minutes
- Sensor Life: approx. 10 year

lifetime (4000 hours) with proper filter changes  
Sensor: Solid electrolyte  
Technology: semi-conductor  
Response Time: Instantaneous (static test) 0.100 sec moving at 3"/sec 0.15 oz/yr leak R134a)  
Sensitivity Levels: MIN- >4 g/yr (0.15oz/yr), MED- 7 g/yr (0.25 oz/yr), MAX- >14 g/yr (0.5 oz/yr)  
Display (5.2 cm): BTN LCD (black) with 10 segment color "pie graph" showing leak size. Backlight included  
Mute Function: Silent mode- display shows leak indication  
Power supply: 4 AA Alkaline or 4 AA NiMH Batteries  
Battery Life: 2.5 hrs continuous (AA Alkaline) 4 hrs continuous (Rechargeable NiMH AA batteries)  
Water protection: IP54. Housing incorporates "O ring" seal, openings inside protected with foam  
Certifications: Complies to standard SAE- J2791, SAE-J2913 EN14624:2012, CE, ROHS, ASHRAE Standard 173 (pending)  
Warm up Time: approx. 30 seconds  
Weight: 1lb. 3.4 oz  
Probe length: 17"  
Length (body): 10"  
Warranty: 2 years  
Made in USA

[http://www.refco.ch/upload/REFCO\\_TRACE\\_REF-LOCATOR.pdf](http://www.refco.ch/upload/REFCO_TRACE_REF-LOCATOR.pdf)

?????? ????????

??? ?????????? ?????????????? ??? ?? ?????? ??????.