

????????? ?????????? ?????????? ?????? Promax MINIMAX-E



????????? ?????????? ?????????? ?????? Promax MINIMAX-E



????????????: ??? ?????????????? ??????

?????

690,00 €

????? ??????? 855,60 €

????? ??????? ?????? 690,00 €

?????????

????????? ?????? 165,60 €

[????????? ??? ?? ???????](#)

???????????

Suitable for A2L Refrigerants like R32 or R1234yf, see separate manual.

RÜCKFÜLL	LIQUID	MASS
KG/MR	KG/MR	KG/MR
R410a	354,00	90,00
R22	340,20	71,20
R134a	271,80	61,80

Features

- Recovers all commonly used CFC, HFC, HCFC refrigerants including A2L like R32 or R1234yF
- Minimum size – maximum performance; ideal for residential and appliance service
- Designed for use with high pressure refrigerants
- 38,5 bar (550 psi) safety cut off switch
- Proprietary “oil-less” compressor capable of handling both liquid and vapor refrigerants
- Ergonomic design for easier handling
- Tough corrosion proof polyethylene blow molded case

- Self purge feature
- Includes filter-drier
- 2,5 m removable cable
- Power Source – 230 V / 50/60 Hz
- Available 115 V / 50/60 Hz
- CE, UL, ARI and TÜV Approvals
- Weight 11 kg
- Dimensions 250 x 222 x 406 mm (11" x 9" x 16")

?????? ?????.

?? ??????? ??????????? ?? ?? ?????? ?????.