

???????? ??????: ?????? ?????? R32 VALUE 100L/min 1/2HP Vi240Y ?????????

???????? ?????? R32 VALUE 100L/min 1/2HP Vi240Y ?????????



?????????: ??? ?????????????? ?????
????

[???????? ?? ?? ??????](#)

??????????

?????? ?????? VALUE Vi240Y 100 lt/min 1/2 ?????????? R32

Model		V-i125Y-R32	V-i240Y-R32	V-i260Y-R32	V-i280Y-R32
Flow Rate	50Hz	2.5CFM	3.5CFM	5.0CFM	7.0CFM
		70L/min	100L/min	142L/min	198L/min
	60HZ	3.0CFM	4.0CFM	6.0CFM	8.0CFM
		84L/min	113L/min	170L/min	226L/min
Ultimate Vacuum	Partial Pressure	2Pa	2*10 ⁻¹ Pa	2*10 ⁻¹ Pa	2*10 ⁻¹ Pa
	Total Pressure	150micron	15micron	15micron	15micron
Power (kw)		1/4HP	1/2HP	3/4HP	1HP
Inlet Port		1/4"Flare	1/4"Flare	1/4"Flare	1/4"Flare
Oil Capacity(L)		250ml	325ml	460ml	500ml
Dimensions(rpm)		290*124*235m m	338*138*248m m	395*145*270m m	395*145*270m m
Weight(Kg)		7.2Kg	11.0Kg	16.6Kg	17.0Kg

?????? ?????????

??? ?????????? ??????????????? ???? ?? ??????? ??????.