

ΚΑΤΑΨΥΞΗ R-404A - 50Hz

ΤΥΠΟΣ	Hp	Volts	dB(A) 10m 5m	T °C	ΘΕΡΜΟΚΡΑΣΙΑ ΕΞΑΤΜΙΣΗΣ						
					-15	-10	-5	0	5	10	15
SIL 2432 Z	3/4	220-240/1/50	27	25	381	539	729	953	1210	1500	1823
			33	32	316	459	631	833	1065	1326	1617
			43	32	214	333	475	641	833	1050	1291
SIL 2440 Z	1	220-240/1/50	30	25	253	622	824	1060	1330	1634	1972
			36	32	378	531	714	926	1169	1442	1746
			43	32	269	398	550	726	927	1153	1405
SIL 2446 Z	1	220-240/1/50	31	25	598	810	1057	1342	1667	2033	2442
			37	32	518	711	935	1191	1479	1803	2164
			43	32	393	557	743	951	1183	1439	1723
SIL 2446 Z	1	400-440/3/50-60	31	25	598	810	1057	1342	1667	2033	2442
			37	32	518	711	935	1191	1479	1803	2164
			43	32	393	557	743	951	1183	1439	1723
SIL 2464Z	1 1/2	220-240/1/50	32	25	821	1095	1416	1785	2199	2654	3145
			38	32	705	956	1249	1583	1959	2365	2805
			43	32	526	739	985	1264	1573	1910	2271
SIL 2464Z	1 1/2	400-440/3/50-60	32	25	821	1095	1416	1785	2199	2654	3145
			38	32	705	956	1249	1583	1956	2365	2805
			43	32	526	739	985	1264	1573	1910	2271
SIL 2480 Z	2	220-240/1/50	33	25	1064	1480	1952	2474	3039	3636	4252
			39	32	862	1263	1711	2201	2726	3278	3844
			43	32	525	902	1311	1750	2214	2696	3187
SIL 2480 Z	2	400-440/3/50-60	33	25	1064	1480	1952	2474	3039	3636	4252
			39	32	862	1263	1711	2201	2726	3278	3844
			43	32	525	902	1311	1750	2214	2696	3187
SIL 2511 Z	3	220-220/3/50-60	39	25	1425	1973	2603	3313	4100	4958	5880
			45	32	1161	1679	2269	2929	3658	4450	5299
			43	32	736	1205	1729	2311	2948	3637	4374
SIL 2516 Z	4	400-440/3/50-60	40	25	2054	2918	3927	5081	6379	7822	9409
			46	32	1607	2410	3335	4379	5545	6831	8238
			43	32	905	1612	2403	3277	4235	5275	6398
SIL 2522 Z	5	220-220/3/50-60	42	25	2530	3516	4629	5870	7239	8734	10357
			48	32	2081	2986	4006	5141	6391	7755	9234
			43	32	1376	2154	3028	3996	5059	6217	7469
SIL 2532 Z	8	400-440/3/50-60	51	25	3426	4950	6642	8498	10519	12703	15046
			57	32	2842	4171	5677	7357	9206	11219	13387
			43	32	3190	4399	5793	7360	9086	10950	
SIL 2544 Z	11	400-440/3/50-60	51	25	4655	6487	8444	10527	12732	15058	17503
			57	32	3862	5467	7216	9105	11129	13280	15547
			43	32	4301	5549	7025	8720	10620	12707	14954

ΔΙΑΣΤΑΣΕΙΣ	ΜΗΚΟΣ	ΒΑΘΟΣ	ΥΨΟΣ
SIL2432/40/46/64Z	896mm	574mm	690mm
SIL2480/2511Z	1108mm	574mm	690mm
SIL2516/22Z SIL2532/44Z	1108mm	574mm	1319mm
	1613mm	574mm	1297mm



ΣΥΝΤΗΡΗΣΗ R-134a - 50Hz



ΤΥΠΟΣ	Hp	Volts	dB(A) T		ΘΕΡΜΟΚΡΑΣΙΑ ΕΞΑΤΜΙΣΗΣ						
			10m	5m	-15	-10	-5	0	5	10	15
											WATT
SIL 4440Y	3/8	220-240/1/50	27	25	536	679	855	1064	1306	1581	1890
			33	32	481	611	772	964	1186	1439	1723
			43	393	504	642	807	998	1216	1460	
SIL 4461Y	1/2	220-240/1/50	29	25	757	970	1221	1512	1845	2221	2643
			35	32	686	882	11112	1380	1688	2038	2431
SIL 4476Y	5/8	220-240/1/50	31	25	910	1164	1457	1790	2164	2582	3042
			37	32	804	1042	1313	1621	1966	2350	2773
SIL 4492Y	3/4	220-240/1/50	31	25	1151	1463	1821	2224	2672	3162	3692
			37	32	1024	1313	1643	2014	2424	2874	3361
SIL 4511Y	1	220-240/1/50	32	25	1458	1832	2252	2715	3217	3753	4317
			38	32	1321	1670	2059	2485	2945	3434	3947
SIL 4518Y	1 1/2	220-240/1/50	34	25	2186	2697	3313	4036	4864	5798	6837
			40	32	1858	2359	2951	3635	4410	5276	6234
SIL 4525Y	2	220-240/1/50	39	25	2843	3512	4276	5134	6086	7133	8274
			45	32	2475	3102	3817	4619	5509	6486	7551
SIL 4528Y	2 1/2	220-220/3/50-60	41	25	3074	4120	5324	6685	8203	9878	11711
			47	32	2645	3586	4680	5926	7326	8878	10583
SIL 4534Y	3	220-220/3/50-60	41	25	3490	4622	5920	7384	9014	10810	12772
			47	32	3007	4020	5192	6525	8017	9668	11479
SIL 4537Y	3 1/4	220-220/3/50-60	41	25	4247	5434	6808	8369	10117	12052	14174
			47	32	3626	4730	6001	7440	9047	10822	12765
SIL 4543Y	3 1/2	220-220/3/50-60	41	25	4790	6114	7598	9241	11043	13004	15124
			47	32	4106	5328	6694	8203	9855	11650	13589
SIL 4556Y	5	400-440/3/50-60	52	25	5461	7211	9192	11401	13836	16495	19372
			58	32	4884	6427	8182	10144	12309	14668	17210
SIL 4568Y	6	400-440/3/50-60	52	25	6012	7920	10021	12315	14798	17467	20319
			58	32	5371	7054	8914	10948	13150	15512	18023
SIL 4574Y	6 1/2	400-440/3/50-60	52	25	6934	9060	11391	13922	16653	19578	22694
			58	32	6191	8068	10132	12377	14798	17385	20123
SIL 4586Y	7 1/4	400-440/3/50-60	52	25	6572	8945	11560	14418	17514	20845	24407
			58	32	5877	7971	10289	12827	15578	18535	21684



ΔΙΑΣΤΑΣΕΙΣ	ΜΗΚΟΣ	ΒΑΘΟΣ	ΥΨΟΣ
SIL 4440/61/76/92Y/4511896mm		574mm	690mm
SIL 4518/25Y	1108mm	574mm	690mm
SIL 4528/34/37/43Y	1108mm	574mm	1319mm
SIL 4556/68/74/86Y	1613mm	574mm	1297mm

ΣΥΝΤΗΡΗΣΗ R-404A – 50Hz

ΣΤΥΠΟΣ	Hp	Volts	dB(A) 10m 5m	T °C	ΘΕΡΜΟΚΡΑΣΙΑ ΕΞΑΤΜΙΣΗΣ						
					-15	-10	-5	0 W	5	10	15
SIL 9450Z	3/7	220-240/1/50	33	25	503	788	974	1188	1431	1703	2003
			39	32	427	678	843	1034	1251	1494	1764
			43	307	506	638	792	968	1166	1387	
SIL 9460Z	1/2	220-240/1/50	33	25	579	903	1115	1360	1638	1950	2294
			39	32	501	787	972	1186	1429	1700	1999
			43	379	604	748	913	1099	1307	1536	
SIL 9480Z	5/8	220-240/1/50	31	25	829	1280	1556	1866	2208	2627	2980
			37	32	721	1140	1391	1671	1979	2312	2671
			43	547	918	1132	1366	1620	1894	2189	
SIL 9510Z	1	220-240/1/50	31	25	1034	1574	1904	2271	2674	3108	3570
			37	32	902	1405	1704	2035	2396	2785	3199
			43	688	1131	1384	1659	1956	2274	2613	
SIL 9513Z	1 1/8	220-240/1/50	31	25	1235	1948	2361	2809	3291	3801	4338
			37	32	1040	1710	2087	2491	2918	3368	3837
			43	726	1329	1649	1982	2326	2680	3045	
SIL 4517Z	1 1/4	220-240/1/50	36	25	-	2142	2608	3118	3668	4254	4870
			42	32	-	1896	2326	2791	3286	3807	4350
			43	-	1498	1871	2262	2668	3086	3515	
SIL 4519Z	1 1/2	220-240/1/50	38	25	-	2767	3362	4016	4729	5497	6321
			44	32	-	2489	3030	3615	4243	4912	5622
			43	-	2039	2492	2966	3459	3971	4501	
SIL 4524Z	2	220-240/1/50	39	25	-	3097	3820	4610	5464	6380	7351
			45	32	-	2706	3370	4086	4853	5668	6530
			43	-	2070	2639	3238	3866	4525	5216	
SIL 4531Z	2 1/2	220-240/1/50	39	25	-	4098	4968	5859	6772	7706	8663
			45	32	-	3539	4393	5245	6098	6956	7820
			43	-	2606	3447	4248	5017	5763	6496	
SIL 4540Z	3	220-240/1/50	39	25	-	4765	5753	6776	7801	8794	9722
			45	32	-	4262	5173	6105	7031	7921	8747
			43	-	3388	4190	4990	5770	6511	7195	
SIL 4546Z	4	220-220/3/50-60	40	25	-	5714	7063	8522	10060	11642	13228
			46	32	-	4875	6108	7434	8826	10257	11692
			43	-	3599	4649	5765	6932	8130	9338	
SIL 4553Z	4 1/2	220-220/3/50-60	40	25	-	6638	8180	9856	11634	13480	15352
			46	32	-	5753	7166	8691	10302	11971	13666
			43	-	4366	5590	6889	8249	9652	11079	
SIL 4561Z	5	220-220/3/50-60	40	25	-	7192	8685	10279	11941	13641	15346
			46	32	-	6238	7617	9080	10605	12167	13746
			43	-	4721	5943	7219	8541	9901	11298	
SIL 4568Z	5	220-220/3/50-60	40	25	-	8597	10370	12287	14317	16425	18574
			46	32	-	7580	9236	11011	12879	14814	16786
			43	-	5972	7442	8992	10608	12278	13988	
SIL 4573Z	6 1/4	400-440/3/50-60	40	25	-	9175	11018	12986	15036	17120	19187
			46	32	-	8105	9791	11574	13241	15293	17149
			43	-	6365	7803	9299	10833	12384	13930	

ΔΙΑΣΤΑΣΕΙΣ	ΜΗΚΟΣ	ΒΑΘΟΣ	ΥΨΟΣ
SIL 9450/60/80/10/13Z SIL	896mm	574mm	690mm
4517/19/24/31/40Z SIL	1108mm	574mm	690mm
4546/53/61/68/73Z	1108mm	574mm	1319mm



ΣΥΝΤΗΡΗΣΗ R-404a - 50Hz

ΤΥΠΟΣ	Hp	Volts	dB(A)		T °C	ΘΕΡΜΟΚΡΑΣΙΑ ΕΞΑΤΜΙΣΗΣ							
			10m	5m		-15	-10	-5	0	5	10	15	
SIL 4590Z	7 1/2	400-440/3/50-60	51	25	-	10772	13357	16001	18702	21453	24245		
			57	32	--	9479	11722	14010	16334	18679	21020	2673	
			43			9501	11350	13202	15026	16776			
SIL 4610Z	9	400-440/3/50-60	51	25	-	11697	14596	17643	20832	24157	27604		
			57	32	--	10311	12828	15468	18217	21053	23942		
			43			8363	10423	12567	14767	16977	19124		
SIL 4612Z	10	400-440/3/50-60	51	25	-	14420	17597	20829	24113	27439	30796		
			57	32	--	12686	15441	18234	21052	23875	26672	10270	
			43			12514	14766	17000	19174	-			
SIL 4614Z	12	400-440/3/50-60	51	25	-	16898	20801	24557	28158	31600	34868		
			57	32	--	14851	18242	21483	24563	27461	30147	12027	
			43			14777	17374	19790	21984	-			
SIL 4615Z	12 1/2	400-440/3/50-60	51	25	-	18983	22050	25582	29572	34010	38878		
			57	32	--	16714	19353	22396	25824	29611	33714		
			43			13518	15672	18133	20866	-			

ΔΙΑΣΤΑΣΕΙΣ	ΜΗΚΟΣ	ΒΑΘΟΣ	ΥΨΟΣ
SIL 4590Z	1613mm	574mm	1297mm
SIL 4610/12/14/15Z	1613mm	574mm	1297mm

